

CBVR 0.6/1.0KV 1.5mm² SHANGHAI HANKE DIANXIAN YOUXIAN GONGSI



应用范围

适用于额定电压600/1000V及以下
船用电线电缆。

APPLICATIONS

Marine wires and cables with rated voltage of not more than
600/1000V.

电线结构

多股细束绞镀锌铜丝导体；
PVC绝缘。

WIRE MAKE-UP

Multi-stranded tincopper conductor；
PVC insulation

技术参数

- 温度范围：-10℃ ~ +80℃
- 额定电压：U₀/U 600/1000V
- 符合标准：企标
- 导体标准：GB/T 3956-1997 第5种

TECHNICAL DATA

- Operating Temp.: -10℃ ~ +80℃
- Rated Voltage: U₀/U 600/1000V
- Governing Standards: Enterprise standard
- Conductor Standards: Category 2 in GB/T 3956-1997

导体截面 Cross Section mm ²	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
0.5	28/0.15	3.21	3.6	16.3
0.75	42/0.15	3.46	3.9	20.0
1	32/0.20	3.81	4.5	25.1
1.5	30/0.25	4.00	4.8	30.7
2.5	50/0.25	4.50	5.4	43.4
4	56/0.30	5.18	6.0	62.5
6	84/0.30	5.85	7.4	86.7
10	84/0.40	7.01	8.6	140
16	126/0.40	8.19	10.5	201
25	196/0.40	9.88	12.1	307
35	276/0.40	12.02	15.2	426
50	396/0.40	13.23	17.3	586
70	360/0.50	15.53	20.5	817
95	475/0.50	17.79	22.2	1068