

通信传输电缆系列 COMMUNICATION CABLES

HJYVB 2×0.2mm<sup>2</sup> SHANGHAI HANKE DIANXIAN YOUXIAN GONGSI



RG-6/U CATV SHANGHAI HANKE DIANXIAN YOUXIAN GONGSI



应用范围

适用于数字、音频、视频信号的传输。

APPLICATIONS

Intended for digital, audio, video signal transmission

电线结构

单根、多股裸束绞铜丝或镀银铜丝；  
PE绝缘，铝箔绕包及铜丝编织屏蔽，PVC护套。

WIRE MAKE-UP

Multi-stranded fine bare copper/silver-coated copper single conductor  
PE insulation, aluminum foil worming and copper mesh shield, PVC sheath

技术参数

- ☒ 温度范围：-10℃ ~ +70℃
- ☒ 符合标准：企标
- ☒ 导体标准：IEC 60228 1、6类

TECHNICAL DATA

- ☒ Operating Temp.: -10℃ ~ +70℃
- ☒ Governing Std.: Enterprise standards
- ☒ Conductor Std.: Category 1, 6 in IEC 60228

导体截面 Cross Section 芯数 × mm <sup>2</sup> Core No. × mm <sup>2</sup>	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
<b>(HJYVB) 电话连接及音频传输电缆</b>				
2×0.2	2×1/0.50	2.10×3.00	2.5×3.7	11.8
<b>(HJYV) 电话连接及音频传输电缆</b>				
4×0.2	4×1/0.50	3.40	3.70	23.1
<b>(SP) 音箱电线</b>				
2×0.8	2×100/0.10	3.32×6.84	3.5×7.2	37.3
2×1.6	2×200/0.10	4.52×9.34	4.8×9.8	69.6
2×2.4	2×300/0.10	5.63×11.66	5.9×12.3	106

产品型号 Product Model	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
RG-6/U CATV	1/1.02	7.20	7.5	55.1
RG-8/U	7/0.73	10.00	10.3	167
RG-11/U	7/0.40	10.00	10.3	150
RG-58C/U	19/0.18	4.65	4.9	39.0