

UL CUL 认可号:
E255620



表面印字: E255620 AWM2464 80°C 300V VW-1 × ×AWG SHHKW AWM I A 80°C 300V FT-1

应用范围

适用于广播、视听、仪器、电脑等设备的连接线。

APPLICATIONS

For wiring of broadcaster, audio-visual unit, instruments, computers.

电线结构

多股细束绞裸铜丝或镀锡铜丝导体, PVC绝缘、护套;
铝箔绕包加铜丝编织, 屏蔽间加地线。

WIRE MAKE-UP

Multi-stranded fine bare copper/tincopper conductor
PVC insulation, PVC sheath,
aluminum foil wormings, earth wire between shields

技术参数

温度范围: 80°C
额定电压: 300V
符合标准: UL 758、1581

TECHNICAL DATA

Operating Temp.: 80°C
Rated Voltage: 300V
Governing Std.: UL 758, 1581

规格 Size 芯数 × AWG Core No × AWG	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
3 × 28	3 × 7/0.127	4.05	4.4	26.7
4 × 28	4 × 7/0.127	4.45	4.8	30.6
5 × 28	5 × 7/0.127	4.55	4.9	34.7
6 × 28	6 × 7/0.127	4.85	5.2	39.0
7 × 28	7 × 7/0.127	5.05	5.4	41.1
8 × 28	8 × 7/0.127	5.25	5.6	45.5
9 × 28	9 × 7/0.127	5.35	5.7	50.6
10 × 28	10 × 7/0.127	5.65	9.0	56.0
15 × 28	15 × 7/0.127	6.25	6.6	71.6
25 × 28	25 × 7/0.127	7.90	8.3	106
37 × 28	37 × 7/0.127	8.65	9.2	140
50 × 28	50 × 7/0.127	9.80	10.4	190
3 × 26	3 × 7/0.16	4.25	4.6	33.5
4 × 26	4 × 7/0.16	4.55	4.9	37.7
5 × 26	5 × 7/0.16	4.85	5.2	43.1
6 × 26	6 × 7/0.16	5.05	5.5	48.8
7 × 26	7 × 7/0.16	5.25	5.6	51.8
8 × 26	8 × 7/0.16	5.45	5.8	57.6
9 × 26	9 × 7/0.16	5.85	6.2	64.4
10 × 26	10 × 7/0.16	6.10	6.5	70.4
15 × 26	15 × 7/0.16	6.80	7.2	92.7
25 × 26	25 × 7/0.16	8.35	8.9	139
37 × 26	37 × 7/0.16	9.45	10.0	186
50 × 26	50 × 7/0.16	10.70	11.3	240

国外标准电线电缆系列 FOREIGN STANDARDS-BASED WIRES & CABLES

(续)

规格 Size 芯数 × AWG Core No × AWG	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
3×24	3×7/0.203	4.45	4.8	37.1
4×24	4×7/0.203	4.95	5.3	43.3
5×24	5×7/0.203	5.45	5.8	49.8
6×24	6×7/0.203	5.45	5.8	56.5
7×24	7×7/0.203	5.55	5.9	60.4
8×24	8×7/0.203	5.75	6.1	67.2
9×24	9×7/0.203	6.15	6.5	75.3
10×24	10×7/0.203	6.50	6.9	82.4
15×24	15×7/0.203	7.15	7.7	109
25×24	25×7/0.203	8.85	9.4	167
37×24	37×7/0.203	10.0	10.6	224
50×24	50×7/0.203	11.60	12.2	310
3×22	3×7/0.254	5.15	5.5	49.7
4×22	4×7/0.254	5.45	5.8	58.8
5×22	5×7/0.254	5.95	6.3	68.4
6×22	6×7/0.254	6.15	6.5	78.3
7×22	7×7/0.254	6.15	6.5	84.2
8×22	8×7/0.254	6.75	7.1	90.0
9×22	9×7/0.254	7.05	7.6	105
10×22	10×7/0.254	7.15	7.7	117
15×22	15×7/0.254	8.05	8.6	157
25×22	25×7/0.254	10.35	10.9	260
37×22	37×7/0.254	11.60	12.2	340
50×22	50×7/0.254	13.20	13.8	420
2×18	2×41/0.16	6.30	6.7	69.2
3×18	3×41/0.16	6.40	6.8	84.3
4×18	4×41/0.16	7.05	7.6	102
5×18	5×41/0.16	7.65	8.2	119